

# H15SX | Scissor Lift

## Working height

**15.0m**

Closed length	4.18m
Closed height	2.77m
Stowed height (guardrails lowered)	1.91m
Closed width	2.25m
Platform size	4.00m x 1.89m
Platform length (deck extended)	6.00m
Max SWL	500kg
Weight	6340kg


## Alternative machines

GS43

## Manufacturer

Haulotte

## Working envelope



15.0m

## Standard features



## Optional extras



**0345 745 0000**

[nationwideplatforms.co.uk](http://nationwideplatforms.co.uk)

**Nationwide  
Platforms**  
A **LOXAM** Company

# Understanding this Product Specification Sheet

This product specification sheet is designed to help you better understand the capabilities and key features of the piece of equipment and whether it will meet your requirements.

The working envelope with height/reach indicator provides a quick visual reference to assist your equipment selection.

If you are unsure about any aspect of this piece of equipment, or would like more information to assist with your selection, please call our expertly trained staff on **0345 745 0000**

## Height and outreach

Working height Horizontal outreach

**AMWP11.5-8100** | Boom Lift

<b>Working height</b>	11.2m	<b>Alternative machines</b>
<b>Horizontal outreach</b>	3m	Star10
<b>Closed length</b>	2.53m	Star10A
<b>Closed height</b>	1.92m	<b>Manufacturer</b>
<b>Closed width</b>	1m	Drift
<b>Rotation</b>	345°	
<b>Platform height</b>	0.2m	
<b>Max. lift</b>	200kg	
<b>Weight</b>	2000kg	
<b>Deck size</b>	0.62m x 0.87m	

**Working envelope**

0 2 4 6 8 10 12
0 2 4 6 8 10 12

**Standard features**

**Optional extras**

**0345 745 0000**  
nationwideplatforms.co.uk
**Nationwide Platforms**  
A LINAM Company

## Standard features

- |                               |                   |                          |                           |
|-------------------------------|-------------------|--------------------------|---------------------------|
| Battery power                 | IPAF licence type | Straight telescopic boom | Self drive                |
| Diesel power                  | IPAF licence type | Non-marking tyres        | J1B rotation              |
| Lithium battery               | IPAF licence type | Outrigger legs           | IPAF driving licence type |
| Hybrid power                  | IPAF licence type | Maximum people in cage*  | Power to platform         |
| Dual fuel option              | IPAF licence type | Push around vehicles     | Generator                 |
| Gas power option              | Tracked           | Operator powered         |                           |
| Rough terrain (2 wheel drive) | Mast boom         | Indoor use only          |                           |
| Rough terrain (4 wheel drive) | Articulating boom | Indoor/Outdoor           |                           |

## Optional extras

- |               |              |                               |                      |
|---------------|--------------|-------------------------------|----------------------|
| SkySiren®     | SkyRakPlus®  | SkyRakEdge™                   | Generator            |
| SkySiren® PCS | SkyRakBoom®  | SkyShield™                    | Camera pod           |
| SkySentry®    | SkyRakMulti™ | SkyScreen™                    | Circular camera cage |
| SkyRak®       | SkyTel™      | Material handling attachments | Wendy lighting frame |

\*The number refers to indoor or outdoor uses. Call us for details.

Please note that all technical information referred to in this document is intended for guidance purposes only and does not act as a replacement for the manufacturer's specification or equipment user guides which should be referred to prior to placing your order. No responsibility can be accepted in the event that this document contains any errors, omissions or data that is different from that in the manufacturer's specification or equipment user guides.